

# Rolls



## FLOODED DEEP CYCLE BATTERY

**4 KS 25P**



Series	5000	Warranty	5 Years
Volts	4	BCI	SPEC
Cells	2	Plates/Cell	25
Terminal Type	Flag		
Included Hardware	S/S Hex Cap Screw, Nut, Lock & Flat Washer		
Size & Thread	5/16"-18		
Cables	19" 4/0 interconnect cables *RE incl.		

### Charge

Charge Voltage Range	2.45-2.5 V/cell @ 25°C (77°F)
Float Voltage Range	2.25 V/cell @ 25°C (77°F)
Self-Discharge Rate	5%-10% per month at 25°C (77°F)

### Capacity

Cold Crank Amps (CCA) 0°F / -17°C	3305
Marine Crank Amps (MCA) 32°F / 0°C	4131
Reserve Capacity (RC @ 25A)	3370 Minutes
Reserve Capacity (RC @ 75A)	1123 Minutes

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	<b>1811 AH</b>	<b>18.11 A</b>
@ 72 Hour Rate	<b>1713 AH</b>	<b>23.79 A</b>
@ 50 Hour Rate	<b>1622 AH</b>	<b>32.43 A</b>
@ 20 Hour Rate	<b>1404 AH</b>	<b>70.20 A</b>
@ 15 Hour Rate	<b>1306 AH</b>	<b>87.05 A</b>
@ 10 Hour Rate	<b>1250 AH</b>	<b>124.96 A</b>
@ 8 Hour Rate	<b>1207 AH</b>	<b>150.93 A</b>
@ 5 Hour Rate	<b>1123 AH</b>	<b>224.64 A</b>
@ 1 Hour Rate	<b>632 AH</b>	<b>631.80 A</b>

Amphere hour capacity ratings based on specific gravity of 1.280. Reduce capacities 5% for specific gravity of 1.265 and 10% for 1.250.

### Specifications




SAI GLOBAL  
ISO 9001  
Quality

Weight	142.5 kg	314 lbs
Length	40 cm	15.75"
Width	27 cm	10.63"
Height Inc. Term.	62.9 cm	24.75"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process, battery components & electrolyte levels.

Electrolyte Reserve	95 mm	3.75"
Container (Inner)	Polypropylene	
Cover (Inner)	Polypropylene - heat sealed to inner container	
Container (Outer)	High Density Polyethylene	
Cover (Outer)	High Density Polyethylene snap fit to outer container	
Handles	Molded	

### Cycle Life vs. Depth of Discharge



### Voltage vs. Depth of Discharge

