



M8

Series	AGM-S	Warranty	See Warranty Terms
Volts	8	BCI	GC8
Cells	4		
Terminal Type		DT	
Included Hardware		Stainless Steel Nuts & Bolts	
Size & Thread		M8	

### Charge

Charge Voltage Range	2.45 V/cell @ 25°C (77°F)
Float Voltage Range	2.3 V/cell @ 25°C (77°F)
Recommended Charge Current Capacity (String)	40 A
Maximum Charge Current (String)	60 A
Self-Discharge Rate	Less than 2% per month at 25°C (77°F)
Internal Resistance	3 mΩ

### Capacity

Cold Crank Amps (CCA) 0°F / -17°C	700			
Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	102%	100%	85%	65%

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	<b>230 AH</b>	<b>2.3 A</b>
@ 20 Hour Rate	<b>200 AH</b>	<b>10 A</b>
@ 10 Hour Rate	<b>190 AH</b>	<b>19 A</b>
@ 5 Hour Rate	<b>176 AH</b>	<b>35.2 A</b>

Cut Off Voltage	Constant Current Discharge									
	30 min	1 hr	2 hr	3 hr	4 hr	5 hr	6 hr	8 hr	10 hr	
VPC	110.6	110.6	67.3	51.6	40.9	35.2	29	23.4	19.5	

### Specifications

Certified System




SAI GLOBAL  
ISO 9001  
Quality

Weight	38 kg	84 lbs
Length	26 cm	10.23"
Width	18.2 cm	7.17"
Height Inc. Term.	31.4 cm	12.36"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process, battery components & electrolyte levels.

Container	ABS
Cover	ABS
Handles	Nylon Strap

### Cycle Life vs. Depth of Discharge



### Capacity vs. Temperature

