

FLOODED	MODEL	BCI	20 HR	CCA @ -18°C (0°F)	MCA @ 0°C (32°F)	DIMENSIONS	WEIGHT
2 VOLT						L x W x H (incl terminal)	
SERIES 4000	S-1450	LI6	1124	2729	3411	31.8 cm x 18.1 cm x 43.2 cm	54.5 kg
SERIES 4000	S-1660	LI6	1284	3119	3898	31.8 cm x 18.1 cm x 43.2 cm	57.5 kg
SERIES 4000	S-1860	LI6	1445	3378	4223	31.8 cm x 18.1 cm x 43.2 cm	59 kg
SERIES 4500	S-1400EX	LI6	1000	2438	3048	31.8 cm x 18.1 cm x 43.2 cm	58 kg
SERIES 5000	2 KS 33P	SPEC	1766	4406	5508	39.2 cm x 21.1 cm x 63.0 cm	94 kg
SERIES 5000	2 OS 33P	SPEC	1880	4536	5670	39.2 cm x 21.1 cm x 63.0 cm	100.5 kg
SERIES 5000	2 YS 27P	SPEC	2106	4975	6219	35.6 cm x 22.9 cm x 80.3 cm	111.5 kg
SERIES 5000	2 YS 31P	SPEC	2430	5741	7176	39.4 cm x 22.9 cm x 80.3 cm	129 kg
SERIES 5000	2 YS 62P	SPEC	4860	11482	14352	69.5 cm x 22.9 cm x 80.3 cm	258.5 kg
4 VOLT						L x W x H (incl terminal)	
SERIES 5000	4 CS 17P	SPEC	546	1393	1742	36.5 cm x 21.0 cm x 46.4 cm	58 kg
SERIES 5000	4 KS 21P	SPEC	1104	2754	3443	40.0 cm x 23.8 cm x 62.9 cm	121 kg
SERIES 5000	4 KS 25P	SPEC	1350	3305	4131	40.0 cm x 27.0 cm x 62.9 cm	142.5 kg
SERIES 5000	4 KS 27P	SPEC	1460	3580	4475	40.0 cm x 27.0 cm x 62.9 cm	153.5 kg
6 VOLT						L x W x H (incl terminal)	
SERIES 4000	EHW 210	GC2	210	547	684	25.9 cm x 18.1 cm x 27.9 cm	28 kg
SERIES 4000	EHW 230	GC2	230	625	781	25.9 cm x 18.1 cm x 27.9 cm	31.5 kg
SERIES 4000	EIW 250	GC2H	250	710	888	25.9 cm x 18.1 cm x 29.0 cm	32 kg
SERIES 4000	EIW 280	SPEC	281	799	998	29.8 cm x 18.1 cm x 28.6 cm	40 kg
SERIES 4000	NS 305	SPEC	300	738	923	31.1 cm x 18.1 cm x 36.2 cm	44 kg
SERIES 4000	CH 375	LI6	375	910	1137	31.8 cm x 18.1 cm x 42.5 cm	51 kg
SERIES 4000	S-480	LI6	375	910	1137	31.8 cm x 18.1 cm x 42.5 cm	51 kg
SERIES 4000	S-550	LI6	428	1040	1299	31.8 cm x 18.1 cm x 42.5 cm	55.5 kg
SERIES 4000	S-605	LI6	468	1169	1462	31.8 cm x 18.1 cm x 42.5 cm	56.5 kg
SERIES 4000	6 HHG 31P	SPEC	344	1337	1671	52.7 cm x 20.3 cm x 30.2 cm	56.5 kg
SERIES 4000	6 EHG 31P	SPEC	410	1549	1936	52.7 cm x 20.3 cm x 32.4 cm	60 kg
SERIES 4000	6 HHG 9D	SPEC	344	1337	1671	52.7 cm x 22.2 cm x 25.4 cm	56.5 kg
SERIES 4500	S-500EX	LI6	357	871	1088	31.8 cm x 18.1 cm x 42.5 cm	59 kg
SERIES 5000	6 CS 17P	SPEC	546	1393	1742	55.9 cm x 21.0 cm x 46.4 cm	100 kg
SERIES 5000	6 CS 21P	SPEC	683	1742	2177	55.9 cm x 24.8 cm x 46.4 cm	122.5 kg
SERIES 5000	6 CS 25P	SPEC	820	2090	2612	55.9 cm x 28.6 cm x 46.4 cm	144 kg
SERIES 5000	6 CS 27P	SPEC	893	2264	2830	55.9 cm x 28.6 cm x 46.4 cm	155 kg

FLOODED	MODEL	BCI	20 HR	CCA @ -18°C (0°F)	MCA @ 0°C (32°F)	DIMENSIONS	WEIGHT
8VOLT						L x W x H (incl terminal)	
SERIES 4000	8 HHG 21P	SPEC	230	1033	1291	54.0 cm x 18.7 cm x 28.3 cm	53.5 kg
SERIES 4000	8 HHG 25P	SPEC	275	1239	1549	62.2 cm x 18.7 cm x 29.2 cm	59 kg
SERIES 4000	8 M 23P	SPEC	240	891	1114	68.6 cm x 18.4 cm x 30.5 cm	57.5 kg
SERIES 4000	8 HHG 29P	SPEC	300	1446	1807	68.6 cm x 18.4 cm x 30.5 cm	68 kg
SERIES 4000	8 HHG 31P	SPEC	344	1337	1671	68.6 cm x 20.3 cm x 30.2 cm	75.5 kg
SERIES 4000	8 EHG 31P	SPEC	410	1549	1936	68.6 cm x 20.3 cm x 32.4 cm	80.5 kg
SERIES 5000	8 CS 17P	SPEC	546	1393	1742	71.8 cm x 21.0 cm x 46.4 cm	133 kg
SERIES 5000	8 CS 25P	SPEC	820	2090	2612	71.8 cm x 28.6 cm x 46.4 cm	192 kg
SERIES 5000	8 CS 27P	SPEC	893	2264	2830	71.8 cm x 28.6 cm x 46.4 cm	207 kg
12VOLT						L x W x H (incl terminal)	
SERIES 4000	24 M 85	24	85	550	690	27.9 cm x 17.1 cm x 23.8 cm	21.5 kg
SERIES 4000	27 M 105	27	105	660	825	32.1 cm x 17.1 cm x 23.8 cm	24.5 kg
SERIES 4000	31 M 130	31	130	620	775	33.0 cm x 17.1 cm x 24.1 cm	29.5 kg
SERIES 4000	12 HHG 185P	4D MOD	185	713	891	52.7 cm x 22.2 cm x 25.4 cm	55 kg
SERIES 4000	T12 250	92I	210	648	810	39.1 cm x 17.8 cm x 36.5 cm	61 kg
SERIES 4000	12 EHG 210P	4DH	210	778	972	52.7 cm x 22.2 cm x 31.4 cm	62.5 kg
SERIES 4000	12 HHG 325P	8D BOX	325	1069	1337	55.2 cm x 33.7 cm x 28.7 cm	90.5 kg
SERIES 4000	12 EHG 375P	8D BOX	375	1166	1458	55.2 cm x 33.7 cm x 31.0 cm	104 kg
SERIES 4000	12 MD 325P	2 x 27	325	1069	1337	47.0 cm x 38.3 cm x 28.1 cm	90.5 kg
SERIES 4000	12 MD 375P	2 x 27H	375	1166	1458	47.0 cm x 38.3 cm x 31.9 cm	104 kg
SERIES 5000	12 CS 11P	SPEC	357	871	1088	55.9 cm x 28.6 cm x 46.4 cm	123 kg

FLOODED	MODEL	BCI	20 HR	CCA @ -18°C (0°F)	MCA @ 0°C (32°F)	DIMENSIONS	WEIGHT
2 VOLT						L x W x H (incl terminal)	
SERIES 4000	S-1450	LI6	1124	2729	3411	12.5" x 7.13" x 17"	120 Lbs
SERIES 4000	S-1660	LI6	1284	3119	3898	12.5" x 7.13" x 17"	127 Lbs
SERIES 4000	S-1860	LI6	1445	3378	4223	12.5" x 7.13" x 17"	130 Lbs
SERIES 4500	S-1400EX	LI6	1000	2438	3048	12.5" x 7.13" x 17"	128 Lbs
SERIES 5000	2 KS 33P	SPEC	1766	4406	5508	15.44" x 8.31" x 24.81"	207 Lbs
SERIES 5000	2 OS 33P	SPEC	1880	4536	5670	15.44" x 8.31" x 24.81"	221.5 Lbs
SERIES 5000	2 YS 27P	SPEC	2106	4975	6219	14" x 9" x 31.63"	246 Lbs
SERIES 5000	2 YS 31P	SPEC	2430	5741	7176	15.5" x 9" x 31.63"	284.5 Lbs
SERIES 5000	2 YS 62P	SPEC	4860	11482	14352	27.38" x 9" x 31.63"	570 Lbs
4 VOLT						L x W x H (incl terminal)	
SERIES 5000	4 CS 17P	SPEC	546	1393	1742	14.38" x 8.25" x 18.25"	128 Lbs
SERIES 5000	4 KS 21P	SPEC	1104	2754	3443	15.75" x 9.38" x 24.75"	267 Lbs
SERIES 5000	4 KS 25P	SPEC	1350	3305	4131	15.75" x 10.63" x 24.75"	314 Lbs
SERIES 5000	4 KS 27P	SPEC	1460	3580	4475	15.75" x 10.63" x 24.75"	338.5 Lbs
6 VOLT						L x W x H (incl terminal)	
SERIES 4000	EHW 210	GC2	210	547	684	10.19" x 7.13" x 11"	61.5 Lbs
SERIES 4000	EHW 230	GC2	230	625	781	10.19" x 7.13" x 11"	69.5 Lbs
SERIES 4000	EIW 250	GC2H	250	710	888	10.19" x 7.13" x 11.40"	70.5 Lbs
SERIES 4000	EIW 280	SPEC	281	799	998	11.75" x 7.13" x 11.25"	88 Lbs
SERIES 4000	NS 305	SPEC	300	738	923	12.25" x 7.13" x 14.25"	97 Lbs
SERIES 4000	CH 375	LI6	375	910	1137	12.5" x 7.13" x 16.75"	112.5 Lbs
SERIES 4000	S-480	LI6	375	910	1137	12.5" x 7.13" x 16.75"	112.5 Lbs
SERIES 4000	S-550	LI6	428	1040	1299	12.5" x 7.13" x 16.75"	122.5 Lbs
SERIES 4000	S-605	LI6	468	1169	1462	12.5" x 7.13" x 16.75"	124.5 Lbs
SERIES 4000	6 HHG 31P	SPEC	344	1337	1671	20.75" x 8" x 11.88"	124.5 Lbs
SERIES 4000	6 EHG 31P	SPEC	410	1549	1936	20.75" x 8" x 12.75"	132.5 Lbs
SERIES 4000	6 HHG 9D	SPEC	344	1337	1671	20.75" x 8.75" x 10"	124.5 Lbs
SERIES 4500	S-500EX	LI6	357	871	1088	12.5" x 7.13" x 16.75"	130 Lbs
SERIES 5000	6 CS 17P	SPEC	546	1393	1742	22" x 8.25" x 18.25"	220.5 Lbs
SERIES 5000	6 CS 21P	SPEC	683	1742	2177	22" x 9.75" x 18.25"	271 Lbs
SERIES 5000	6 CS 25P	SPEC	820	2090	2612	22" x 11.25" x 18.25"	317.5 Lbs
SERIES 5000	6 CS 27P	SPEC	893	2264	2830	22" x 11.25" x 18.25"	341.5 Lbs

FLOODED	MODEL	BCI	20 HR	CCA @ -18°C (0°F)	MCA @ 0°C (32°F)	DIMENSIONS	WEIGHT
8VOLT						L x W x H (incl terminal)	
SERIES 4000	8 HHG 21P	SPEC	230	1033	1291	21.25" x 7.38" x 11.13"	118 Lbs
SERIES 4000	8 HHG 25P	SPEC	275	1239	1549	24.5" x 7.38" x 11.5"	130 Lbs
SERIES 4000	8 M 23P	SPEC	240	891	1114	27" x 7.25" x 12"	127 Lbs
SERIES 4000	8 HHG 29P	SPEC	300	1446	1807	27" x 7.25" x 12"	150 Lbs
SERIES 4000	8 HHG 31P	SPEC	344	1337	1671	27" x 8" x 11.88"	167 Lbs
SERIES 4000	8 EHG 31P	SPEC	410	1549	1936	27" x 8" x 12 3/4"	178 Lbs
SERIES 5000	8 CS 17P	SPEC	546	1393	1742	28.25" x 8.25" x 18.25"	293 Lbs
SERIES 5000	8 CS 25P	SPEC	820	2090	2612	28.25" x 11.25" x 18.25"	423.5 Lbs
SERIES 5000	8 CS 27P	SPEC	893	2264	2830	28.25" x 11.25" x 18.25"	456 Lbs
12VOLT						L x W x H (incl terminal)	
SERIES 4000	24 M 85	24	85	550	690	11" x 6.75" x 9.38"	47.5 Lbs
SERIES 4000	27 M 105	27	105	660	825	12.63" x 6.75" x 9.38"	54 Lbs
SERIES 4000	31 M 130	31	130	620	775	13" x 6.75" x 9.50"	65 Lbs
SERIES 4000	12 HHG 185P	4D MOD	185	713	891	20.75" x 8.75" x 10"	121.5 Lbs
SERIES 4000	T12 250	921	210	648	810	15.38" x 7" x 14.38"	134.5 Lbs
SERIES 4000	12 EHG 210P	4DH	210	778	972	20.75" x 8.75" x 12.38"	138 Lbs
SERIES 4000	12 HHG 325P	8D BOX	325	1069	1337	21.75" x 13.25" x 11.31"	199.5 Lbs
SERIES 4000	12 EHG 375P	8D BOX	375	1166	1458	21.75" x 13.25" x 12.19"	229.5 Lbs
SERIES 4000	12 MD 325P	2 x 27	325	1069	1337	18.50" x 15.06" x 11.06"	199.5 Lbs
SERIES 4000	12 MD 375P	2 x 27H	375	1166	1458	18.50" x 15.06" x 12.56"	229.5 Lbs
SERIES 5000	12 CS 11P	SPEC	357	871	1088	22" x 11.25" x 18.25"	271 Lbs