



S6-370AGM

6 VOLTS



CAPACITY 335 AH

HOUR RATE:	SPECIFIC GRAVITY	CAPACITY / AMP HOUR	CURRENT / AMPS
@ 100 HOUR RATE	1.280	370	3.70
@ 20 HOUR RATE	1.280	335	16.75
@ 10 HOUR RATE	1.280	278	27.80
@ 8 HOUR RATE	1.280	269	33.63
@ 5 HOUR RATE	1.280	254	50.80

AT 77°F / 25°C

CAPACITY AFFECTED BY TEMPERATURE (20 HR RATE)

104°F / 40°C	102%
77°F / 25°C	100%
32°F / 0°C	85%
5°F / -15°C	65%

SELF-DISCHARGE 77°F / 25°C

CAPACITY AFTER 3 MONTHS	91%
CAPACITY AFTER 6 MONTHS	82%
CAPACITY AFTER 12 MONTHS	64%

WEIGHT:	46.70 kg	105 Lbs.
LENGTH:	295 mm	11 3/5 Inches
WIDTH:	179 mm	7 Inches
HEIGHT*:	365 mm	14 3/8 Inches

* including terminal

CONTAINER:	ABS
COVER:	ABS
TERMINALS:	DT - Auto Post & M8 Button Terminal
HANDLES:	Rope / Molded Plastic

RESERVE CAPACITY (RC @ 25A):	695 Minutes
INTERNAL RESISTANCE (77°F / 25°C)	1.6 m Ω
MAXIMUM DISCHARGE CURRENT	2000 A
RECOMMENDED CHARGE CURRENT:	77 A
MAX CHARGE CURRENT:	100 A



SAI GLOBAL
ISO 9001
Quality

CHARGING constant voltage	CYCLE:	7.25V ~ 7.45V / 77°F / 25°C
	FLOAT:	6.8V ~ 6.9V / 77°F / 25°C

CYCLE LIFE VS. DEPTH OF DISCHARGE

