




# FLOODED CELL SPACING

## Flooded Cell Spacing for Automatic Watering Systems

A = END OF CASE TO CELL  
B = CELL TO CELL  
C = SIDE OF CASE TO CELL



MODEL	A		B		C	
	END OF CASE TO CELL		CELL TO CELL		SIDE TO CELL	
	MM	INCHES	MM	INCHES	MM	INCHES
<b>6V L16</b> S-480, S-550, S-605, S-500EX FC-420, CH375, 6FS350, 6FS375 6FS400, 6FS425, 6FS465	89 mm	3 1/2"	70 mm	2 3/4"	93 mm	3 2/3"
<b>2V L16</b> S-1450, S-1660, S-1860, S-1400EX	156 mm	6 1/8"	SINGLE CELL		90 mm	3 4/7"
2 KS 33P	149 mm	5 6/7"			106 mm	4 1/6"
2 OS 33P	149 mm	5 6/7"			106 mm	4 1/6"
2 YS 27P, 2 YS 31P	133 mm	5 1/4"			114 mm	4 1/2"
2 YS 62P	133 mm	5 1/4"			302 mm	11 7/8"
4 CS 17P	94 mm	3 2/3"	178 mm	7 "	105 mm	4 1/8"
4 KS 21P	121 mm	4 3/4"	159 mm	6 1/4"	125 mm	5 "
4 KS 25P, 4 KS 27P	121 mm	4 3/4"	159 mm	6 1/4"	135 mm	5 1/3"
6 CS 17P	121 mm	4 3/4"	159 mm	6 1/4"	105 mm	4 1/8"
6 CS 21P	121 mm	4 3/4"	159 mm	6 1/4"	124 mm	4 7/8"
6 CS 25P, 6 CS 27P	121 mm	4 3/4"	159 mm	6 1/4"	143 mm	5 5/8"
6 HHG 31P, EHG 31P	98 mm	3 7/8"	165 mm	6 1/2"	102 mm	4 "
S-290, 6 FS 210/230, EIW 230	61 mm	2 2/5"	74 mm	2 8/9"	89 mm	3 1/2"
S-330, 6 FS 250, EHW 250	61 mm	2 2/5"	74 mm	2 8/9"	89 mm	3 1/2"
6 FS 260, EIGH 262	89 mm	3 1/2"	70 mm	2 3/4"	89 mm	3 1/2"
6 FS 300, NS 305	89 mm	3 1/2"	70 mm	2 3/4"	90 mm	3 4/7"
8 CS 17P	102 mm	4 "	159 mm	6 1/4"	105 mm	4 1/8"
8 CS 25P, 8 CS 27P	121 mm	4 3/4"	159 mm	6 1/4"	143 mm	5 5/8"
8 CH 23P, 8 CH 33P	102 mm	4 "	159 mm	6 1/4"	105 mm	4 1/8"
8 HHG 21P	75 mm	3 "	127 mm	5 "	93 mm	3 2/3"
8 HHG 25P	92 mm	3 5/8"	146 mm	5 3/4"	81 mm	3 1/5"
8 HHG 29P	95 mm	3 3/4"	159 mm	6 1/4"	92 mm	3 5/8"
8 HHG 31P, 8 EHG, 31P	95 mm	3 3/4"	165 mm	6 1/2"	102 mm	4 "
S-105, 24 M 85, 12 FS 80	NOT COMPLIANT WITH WATERING SYSTEMS					
S-140, 27 M 105, 12 FS 105	NOT COMPLIANT WITH WATERING SYSTEMS					
S-160, 12 FS 125, 30 H 125	40 mm	1 4/7"	51 mm	2 "	86 mm	3 3/8"
S-180, T12 136, 12 FS 135	NOT COMPLIANT WITH WATERING SYSTEMS					
S-260, T12 250, 12 FS 200	40 mm	1 4/7"	64 mm	2 1/2"	Varies	Varies
HT 8D, 12 HHG 8D	102 mm	4 "	162 mm	6 3/8"	93 mm	3 2/3"
12 CS 11P	102 mm	4 "	157 mm	6 1/5"	89 mm	3 1/2"

\* NOTE: BATTERIES SHOULD BE SPACED A MINIMUM 2.54 cm (1") APART TO ALLOW PROPER AIRFLOW.

TO REQUEST CELL SPACING FOR ADDITIONAL AND/OR CUSTOM FLOODED DEEP CYCLE LEAD ACID MODELS, PLEASE CONTACT OUR SALES DEPARTMENT - SALES@ROLLSBATTERY.COM