



Series	5000	Warranty	See Warranty Terms
Volts	6	BCI	SPEC
Cells	3	Plates/Cell	21
Terminal Type	Flag		
Included Hardware	S/S Hex Cap Screw, Nut, Lock & Flat Washer		
Size & Thread	5/16"-18		

### Charge

Charge Voltage Range	2.45-2.5 V/cell @ 25°C (77°F)
Float Voltage Range	2.25 V/cell @ 25°C (77°F)
Self-Discharge Rate	5%-10% per month at 25°C (77°F)

### Capacity

Cold Crank Amps (CCA) 0°F / -18°C	1742
Marine Crank Amps (MCA) 32°F / 0°C	2177
Reserve Capacity (RC @ 25A)	1705 Minutes
Reserve Capacity (RC @ 75A)	568 Minutes

Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	105%	100%	75%	50%

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	<b>916 AH</b>	<b>9.16 A</b>
@ 72 Hour Rate	<b>867 AH</b>	<b>12.04 A</b>
@ 50 Hour Rate	<b>820 AH</b>	<b>16.41 A</b>
@ 20 Hour Rate	<b>710 AH</b>	<b>35.52 A</b>
@ 15 Hour Rate	<b>661 AH</b>	<b>44.04 A</b>
@ 10 Hour Rate	<b>632 AH</b>	<b>63.22 A</b>
@ 8 Hour Rate	<b>611 AH</b>	<b>76.36 A</b>
@ 5 Hour Rate	<b>568 AH</b>	<b>113.65 A</b>
@ 1 Hour Rate	<b>320 AH</b>	<b>319.64 A</b>

Ampere hour capacity ratings based on specific gravity of 1.280 at 27°C (80°F). Reduce capacities 5% for specific gravity of 1.265 and 10% for 1.250.

### Specifications




Weight	122.5 kg	270 lbs
Length	55.9 cm	22"
Width	24.8 cm	9.75"
Height Inc. Term.	46.4 cm	18.25"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Electrolyte Reserve	95 mm	3.75"
Container (Inner)	Polypropylene	
Cover (Inner)	Polypropylene - heat sealed to inner container	
Container (Outer)	High Density Polyethylene	
Cover (Outer)	High Density Polyethylene snap fit to outer container	
Handles	Molded	

### Cycle Life vs. Depth of Discharge



### Voltage vs. Depth of Discharge

DISCHARGE	0%	25%	50%	75%	100%
20 HR AH RATE	2.10 V	2.05 V	2.02 V	1.96 V	1.75 V
6 HR AH RATE	2.10 V	2.04 V	2.00 V	1.95 V	1.75 V
1 HR AH RATE	2.10 V	2.03 V	1.99 V	1.94 V	1.75 V

### Detailed Illustration

