


FLOODED DEEP CYCLE BATTERY

8 NS 33PR



| | | | |
|---------------|------|-------------|---------|
| Series | 5000 | Warranty | 5 Years |
| Volts | 8 | Design | SLI |
| Cells | 4 | Plates/Cell | 33 |
| Terminal Type | | Flag RR | |

Charge

| | |
|----------------------|---------------------------------|
| Charge Voltage Range | 2.45-2.5 V/cell @ 25°C (77°F) |
| Float Voltage Range | 2.25 V/cell @ 25°C (77°F) |
| Self-Discharge Rate | 5%-10% per month at 25°C (77°F) |

Capacity

| | |
|------------------------------------|--------------|
| Cold Crank Amps (CCA) 0°F / -18°C | 2268 |
| Marine Crank Amps (MCA) 32°F / 0°C | 2835 |
| Reserve Capacity (RC @ 25A) | 1634 Minutes |
| Reserve Capacity (RC @ 75A) | 545 Minutes |

| | | | | |
|--------------------------------|--------------|-------------|------------|-------------|
| Capacity Affect by Temperature | 40°C (104°F) | 25°C (77°F) | 0°C (32°F) | -15°C (5°F) |
| | 105% | 100% | 75% | 50% |

| Hour Rate | Capacity / AMP Hour | Current / AMPs |
|-----------------|---------------------|-----------------|
| @ 100 Hour Rate | 783 AH | 7.83 A |
| @ 72 Hour Rate | 763 AH | 10.59 A |
| @ 50 Hour Rate | 735 AH | 14.71 A |
| @ 20 Hour Rate | 681 AH | 34.05 A |
| @ 15 Hour Rate | 640 AH | 42.68 A |
| @ 10 Hour Rate | 613 AH | 61.29 A |
| @ 8 Hour Rate | 586 AH | 73.21 A |
| @ 5 Hour Rate | 545 AH | 108.96 A |
| @ 1 Hour Rate | 320 AH | 320.07 A |

Ampere hour capacity ratings based on specific gravity of 1.280 at 27°C (80°F). Reduce capacities 5% for specific gravity of 1.265 and 10% for 1.250.

Specifications


| | | |
|--------------------|----------|-----------|
| Weight | 159.5 kg | 351.5 lbs |
| Length | 718 mm | 28.25" |
| Width | 286 mm | 11.25" |
| Height Incl. Term. | 464 mm | 18.25" |

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

| | | |
|---------------------|-------------------------------------------------------|-------|
| Electrolyte Reserve | 143 mm | 5.63" |
| Container (Inner) | Polypropylene | |
| Cover (Inner) | Polypropylene - heat sealed to inner container | |
| Container (Outer) | High Density Polyethylene | |
| Cover (Outer) | High Density Polyethylene snap fit to outer container | |
| Handles | Molded | |

- Plastics are UL94 HB (UL94-V2 available)
- Plastics are impact copolymer rated to ASTM D256, D5420
- Vented design with integral flame arrestor vent caps


Cycle Life vs. Depth of Discharge



Voltage vs. Depth of Discharge

| DISCHARGE | 0% | 25% | 50% | 75% | 100% |
|---------------|--------|--------|--------|--------|--------|
| 20 HR AH RATE | 2.10 V | 2.05 V | 2.02 V | 1.96 V | 1.75 V |
| 6 HR AH RATE | 2.10 V | 2.04 V | 2.00 V | 1.95 V | 1.75 V |
| 1 HR AH RATE | 2.10 V | 2.03 V | 1.99 V | 1.94 V | 1.75 V |

Detailed Illustration



Designed in compliance with applicable BCI, DIN, BS & IEC standards. Tested in compliance to BCI & IEC standards.

intertek
0122624