

Series	Warranty	Ver condiciones de garantía
Terminal Type	M8	
Size & Thread	M8	

Charge

Charge Voltage Range	14,7V @ 25°C (77°F)
Float Voltage Range	13,8V @ 25°C (77°F)
Recommended Charge Current	40 A
Maximum Charge Current	60 A
Self-Discharge Rate	Menos del 2% al mes a 25°C (77°F)
Internal Resistance	4 mΩ

Capacity

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 20 Hour Rate	212 AH	10.6 A
@ 10 Hour Rate	200 AH	20 A
@ 5 Hour Rate	170 AH	34 A

Cut Off Voltage	Constant Current Discharge						
	1 hr	2 hr	3 hr	4 hr	5 hr	8 hr	10 hr
1.8 VPC	105.8	63.4	50	39.7	34	23.9	20

Specifications

 SAI GLOBAL ISO 9001 Quality	Weight	57.5 kg	126.8 lbs
	Length	56.0 cm	22.1"
	Width	12.5 cm	4.92"
	Height Inc. Term.	31.6 cm	12.4"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Container	ABS
Cover	ABS
Handles	Cuerda / Mango de plástico

Rev.#1