



Series	AGM-S	Warranty	See Warranty Terms
Volts	6	BCI	27
Cells	3		
Terminal Type	M8 incl. TP08		
Included Hardware	M8 stainless bolts & washers & TP08 adapter		
Size & Thread	M8		

Charge

Charge Voltage Range	2.45 V/cell @ 25°C (77°F)
Float Voltage Range	2.3 V/cell @ 25°C (77°F)
Recommended Charge Current	45 A
Maximum Charge Current	70 A
Self-Discharge Rate	Less than 2% per month at 25°C (77°F)
Internal Resistance	1.3 mΩ

Capacity

Capacity Affect by Temperature		40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
		102%	100%	85%	65%
Hour Rate	Capacity / AMP Hour	Current / AMPs			
@ 100 Hour Rate	260 AH	2.6 A			
@ 20 Hour Rate	234 AH	11.7 A			
@ 10 Hour Rate	220 AH	22 A			
@ 5 Hour Rate	192 AH	38.4 A			

Specifications




Weight	32 kg	70.5 lbs
Length	30.6 cm	12.04"
Width	16.8 cm	6.61"
Height Inc. Term.	22.7 cm	8.94"


Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Container	ABS
Cover	ABS
Handles	Nylon Strap

Cycle Life vs. Depth of Discharge



Capacity vs. Temperature



Detailed Illustration

