




# Flooded Cell Spacing for Automatic Watering Systems

A = END OF CASE TO CELL  
B = CELL TO CELL  
C = SIDE OF CASE TO CELL



MODEL	A		B		C	
	END OF CASE TO CELL		CELL TO CELL		SIDE TO CELL	
	MM	INCHES	MM	INCHES	MM	INCHES
S6 L16, S6 L16-HC, S6 L16-SC, S6 L16-EX, 6 FS L16, 6 FS L16-HC	89 mm	3 1/2"	70 mm	2 3/4"	93 mm	3 2/3"
S2 L16, S2-L16-HC, S2-L16-SC, S2 L16-EX	156 mm	6 1/8"	SINGLE CELL		90 mm	3 4/7"
2 KS 33P	149 mm	5 6/7"			106 mm	4 1/6"
2 OS 33P	149 mm	5 6/7"			106 mm	4 1/6"
2 YS 27P, 2 YS 31P	133 mm	5 1/4"			114 mm	4 1/2"
2 YS 62P	133 mm	5 1/4"	302 mm	11 7/8"	105 mm	4 1/8"
4 CS 17P	94 mm	3 2/3"	178 mm	7"	105 mm	4 1/8"
4 KS 21P	121 mm	4 3/4"	159 mm	6 1/4"	125 mm	5"
4 KS 25P, 4 KS 27P	121 mm	4 3/4"	159 mm	6 1/4"	135 mm	5 1/3"
6 CS 17P	121 mm	4 3/4"	159 mm	6 1/4"	105 mm	4 1/8"
6 CS 21P	121 mm	4 3/4"	159 mm	6 1/4"	124 mm	4 7/8"
6 CS 25P, 6 CS 27P	121 mm	4 3/4"	159 mm	6 1/4"	143 mm	5 5/8"
6 HHG 31P, EHG 31P	98 mm	3 7/8"	165 mm	6 1/2"	102 mm	4"
S6 GC2, S6 GC2-HC, 6FS GC, 6FS GC-HC, 6FS GC-SC	61 mm	2 2/5"	69 mm	2 3/4"	89 mm	3 1/2"
S6 145, 6 FS 145	61 mm	2 2/5"	69 mm	2 3/4"	89 mm	3 1/2"
6 FS 250-SC	83 mm	3 1/4"	70 mm	2 3/4"	89 mm	3 1/2"
S6 305, 6 FS 305-HC 6 FS 305-SC	89 mm	3 1/2"	70 mm	2 3/4"	89 mm	3 1/2"
8 FS GC, 8 FS GC-HC	35 mm	1 3/8"	64 mm	2 1/2"	89 mm	3 1/2"
8 CS 17P	102 mm	4 3/4"	159 mm	6 1/4"	105 mm	4 1/8"
8 CS 25P, 8 CS 27P	121 mm	4 3/4"	159 mm	6 1/4"	143 mm	5 5/8"
8 CH 23P, 8 CH 33P	102 mm	4"	159 mm	6 1/4"	105 mm	4 1/8"
8 HHG 21P	75 mm	3"	127 mm	5"	93 mm	3 2/3"
8 HHG 25P	92 mm	3 5/8"	146 mm	5 3/4"	81 mm	3 1/5"
8 HHG 29P	95 mm	3 3/4"	159 mm	6 1/4"	92 mm	3 5/8"
8 HHG 31P, 8 EHG 31P	95 mm	3 3/4"	165 mm	6 1/2"	102 mm	4"
S12 24, 12 FS 24, S12 27, 12 FS 27, S12 31, 12 FS 31	NOT COMPATIBLE WITH WATERING SYSTEMS					
S12 185, 12 FS 185-HC	40 mm	1 4/7"	64 mm	2 1/2"	Varies	Varies
12 FS GC-HC	35mm	1 3/8"	51 mm	2"	Varies	Varies
12 CS 11P	102 mm	4"	157 mm	6 1/5"	89 mm	3 1/2"

\* NOTE: BATTERIES SHOULD BE SPACED A MINIMUM 2.54 cm (1") APART TO ALLOW PROPER AIRFLOW. TO REQUEST CELL SPACING FOR ADDITIONAL AND/OR CUSTOM FLOODED DEEP CYCLE LEAD ACID MODELS, PLEASE CONTACT OUR SALES DEPARTMENT - SALES@ROLLSBATTERY.COM